

ENHANCED MONITORED PDU MODEL: IP-DEI-321C33C932



INPUT



Features	
Meter	True RMS Current Meter, Voltage, Frequency, Power Factor, Active Power, Apparent Power, Total kWh, Sub-total kWh.
Power Monitor	Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, Https, SNMP, DHCP, UDP
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Temp./Humidity	Option Accessory
Event Alert	Email, Trap, Audible Alarm
Specification	
General	
Output	(21) IEC 320 C13 (3) IEC 320 C19
Input	(1) IEC 309 attached power cord, 3 meters long
Protection	(3) 16 AMP Circuit Breaker
Communication	
SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(3) Green LED
Circuit Status	(1) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digit Seven Segments for PDU Identification
Meter	3 Digits Seven Segments
Power Information	
Voltage	+/- 2% @ 90V~260V
Active Power	+/- 2% @ 50W~5000W
Apparent Power	+/- 2% @ 50VA~5000VA
Frequency	+/- 2% @ 45~65Hz
Power Factor	+/- 0.02 @ 0.5~1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/-2% @ 50W~5000W, kh=1.0
Current	Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP
Operation	
Nominal Input Voltage	230V
Output Voltage	200V~ 240V full range
Frequency	50/60Hz full range
Max. Output Current	32A (total); Each Bank 16A; Each Outlet 10A (C13) or 16A (C19)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	1778 x 56 x 44 mm
Weight	4.0 kg

